

TECHNICAL DESCRIPTION
CRANEFRIGOR™ CC02

Date: 26.09.2023
QVO 0459-US
Rev. 03

Technical support: **e-mail:** sales@frigortecamericas.com / **phone:** +1 / (832) 730 - 1894



Figure

CRANEFRIGOR™ CC02

The CRANEFRIGOR™ CC02 cooling unit was developed for reliable and long-term operation under extreme ambient conditions as in steel works, paper factories and foundries. Thanks to its robust structure, a reliable operation is ensured even with heavy shocks.

The CRANEFRIGOR™ series of crane air conditioning units ensure a reliable and efficient production process.

General description

Scope of delivery	Your benefits!
Refrigerant <ul style="list-style-type: none"> Ecological refrigerant Low greenhouse warming potential 	<ul style="list-style-type: none"> Sustainable operation
Compressor <ul style="list-style-type: none"> Hermetically sealed construction Suction-gas-cooled motor Self-regulating oil sump heater 	<ul style="list-style-type: none"> Low maintenance No risk of overheating Ensures lubrication during the start
Liquefier <ul style="list-style-type: none"> Zinc-plated steel housing with epoxy-coated aluminum blades 	<ul style="list-style-type: none"> Excellent heat transfer Shorter maintenance intervals due to special adapted spacing between blades even with extreme dust load Shorter maintenance intervals due to smooth surface
Liquefier fan <ul style="list-style-type: none"> Speed-controlled EC axial fan in industrial construction for high ambient temperatures 	<ul style="list-style-type: none"> Powerful Long runtimes Energy-efficient
Evaporator <ul style="list-style-type: none"> Zinc-plated steel housing with epoxy-coated aluminum blades Cleaning opening / Inspection opening 	<ul style="list-style-type: none"> Excellent heat transfer Shorter maintenance intervals due to special adapted spacing between blades even with extreme dust load Shorter maintenance interval due to smooth surface. Soiling is easily recognized and simple to clean through the opening
Circulating air fan <ul style="list-style-type: none"> EC radial fan, industrial construction 	<ul style="list-style-type: none"> Powerful Long runtimes Energy-efficient and quiet
Air filter <ul style="list-style-type: none"> Large-surface frame filter Filter class COARSE 70 % 	<ul style="list-style-type: none"> Effective filter with long service life Easy to replace and clean
Condensation water separation <ul style="list-style-type: none"> Drip tray primed and powder-coated in RAL 7035 Hose connection for condensation Siphon in condensate line 	<ul style="list-style-type: none"> No corrosion of the tray Defined condensation drainage Avoids the drawing in of contaminated ambient air
Control and power cabinet <ul style="list-style-type: none"> Completely wired, according to VDE Temperature control by thermostat Operational and fault signal outputs Powder-coated RAL 7035 Optional stainless-steel version 	<ul style="list-style-type: none"> The CRANEFRIGOR™ is ready for connection; at the site, you only have to connect the power supply Color scheme with high corrosion protection
Casing <ul style="list-style-type: none"> Robust, welded construction Primed and powder-coated in RAL 7035 Other colors or stainless steel version optional 	<ul style="list-style-type: none"> Long service life Attractive colour scheme with high corrosion protection
Quality assurance <ul style="list-style-type: none"> Leakage test Function test in our plant's test facility 	<ul style="list-style-type: none"> Operational reliability Easy commissioning on site

Options packages:

Material order no.	Scope of delivery	Your benefits!
807 645 807 649	Options packages “Corrosion protection” Corrosion protection package 1 Corrosion protection package 2	<ul style="list-style-type: none"> • Multiple-coated pipes • Housing / Plate parts made of high-quality stainless steel 1.4571 / AISI 316Ti • Multiple-coated pipes
807 653	Option package “Custom” Customer-specific version	<p>Special requirements of a company can be realized, such as:</p> <ul style="list-style-type: none"> • Custom voltages / Network configurations • Heat exchanger version (fully copper, blade spacing and thickness) • Conductor identification • Special coatings • Protection class
807 657 807 661	Options packages “Accessories” Assembly accessories according to specification Spare parts according to specification	<ul style="list-style-type: none"> • Air duct, holding devices, refrigerating accessories • Spare part package

Plant packages:

Material order no.	Scope of delivery	Your benefits!
807 562	Plant package “Overpressure / Fresh air” Filter/Overpressure unit FT15	<ul style="list-style-type: none"> • Filtered fresh air supply, adjustable air volume • Creation of overpressure in the room to be cooled; less dust comes in
807 579	Plant package “Condensation evaporator” Condensation evaporator KV1	<ul style="list-style-type: none"> • No damage due to dripping condensation • No additional power supply necessary • Overload protection

Technical specifications CC02:

Performance data

Cooling performance is included customized in the offer
Heat output is included customized in the offer

Nominal cooling performance:

- At 80 °F (27 °C) room temperature, 52 % rel. room air humidity
95 °F (35 °C) ambient temperature
- Refrigerant R134a / R513A

3.4 kW | 11,600 btu/h

Air flow volume:

1,500 m³/h | 885 cfm

Cooling mode

- Depends on the compressor model size and version
- Depends on the option packages and version of heat exchanger

Temperature range R134a

-5 °C to +70 °C | +25 °F to +160 °F

Temperature range R513A

-5 °C to +70 °C | +25 °F to +160 °F

Sizes and weight

Weight

approx. 90 kg | 200 lbs

Dimensions

type, see dimension sheet

Operating voltage

Further operating voltages upon request

3 ph / 400 V / 50 Hz

3 ph / 460 V / 60 Hz

1 ph / 230 V / 50 Hz

1 ph / 230 V / 60 Hz

Refrigerant

GWP (global warming potential)

R134a / R513A

1430 / 631

Filling quantity / CO₂ equivalent

depends on the unit version

Subject to technical change.