

TECHNICAL DESCRIPTION
CRANEFRIGOR™ TW3

Date: 27.01.2022
QVO 0463-US
Rev. 02

Technical support: **e-mail:** sales@frigortecamericas.com / **phone:** +1 / (832) 730 - 1894



Figure

CRANEFRIGOR™ TW3

The CRANEFRIGOR™ TW3 cooling unit was developed for reliable and long-term operation under extreme ambient conditions as in steel works, paper factories and foundries. Thanks to its robust structure, a reliable operation is ensured even with heavy shocks.

The CRANEFRIGOR™ series of crane air conditioning units ensure a reliable and efficient production process.

General description

Scope of delivery	Your benefits!
Refrigerant - Ecological refrigerant - Low greenhouse warming potential	Sustainable operation
Compressor (made by Copeland) - Hermetically sealed construction - Suction-gas-cooled motor - Self-regulating oil sump heater	- Low maintenance - No risk of overheating - Ensures lubrication during the start - Very good availability of spare parts worldwide
Liquefier Cathodic dip coating	- High corrosion resistance - Shorter maintenance intervals due to special adapted spacing between blades even with extreme dust load - Shorter maintenance intervals due to smooth surface
Liquefier fan Speed-controlled EC axial fan in industrial construction for high ambient temperatures	- Powerful - Long runtimes - Energy-efficient
Evaporator - Zinc-plated steel housing with epoxy-coated aluminum blades - Cleaning opening / Inspection opening	- Excellent heat transfer - Shorter maintenance intervals due to special adapted spacing between blades even with extreme dust load - Shorter maintenance interval due to smooth surface. Soiling is easily recognised and simple to clean through the opening
Circulating air fan Speed-controlled EC radial fan, industrial construction	- Powerful - Long runtimes - Energy-efficient and quiet
Heater Air heater with temperature monitor and safety temperature limiter	- Comfortable room temperature - Frost protection even at standstill or during maintenance work
Output adjustment Regulation of cooling performance by hot-gas bypass	Minimal temperature fluctuations in the cabin
Air filter - Large-area frame filter - Filter class COARSE 90%	- Effective filter with long service life - Easy to replace and clean
Condensation water separation - Drip tray primed and powder-coated in RAL 7035 - Hose connection for condensation - Siphon in condensate line	- No corrosion of the tray - Defined condensation drainage - Avoids the drawing in of contaminated ambient air
Control and power cabinet - Completely wired, according to VDE - Operational and fault signal outputs - Powder-coated RAL 7035 - Climate control box K6 <u>Remarks:</u> Climate control box can be installed anywhere in the cabin	- The CRANEFRIGOR™ is ready for connection; at the site, you only have to connect the power supply - Colour scheme with high corrosion protection Functions climate control box: - Switch on air-conditioning mode - Switch on heating mode - Switch on dehumidification mode (simultaneously cooling and heating) - Digital actual and setpoint display at the regulator - Switch between manual and automatic blower modes

Casing • Robust, welded construction • Primed and powder-coated in RAL 7035 • Other colours or stainless steel version optional	• Long service life • Attractive colour scheme with high corrosion protection
Quality assurance • Leakage test • Function test in our plant's test facility	• Operational reliability • Easy commissioning on site

Options packages:

Material order no.	Scope of delivery	Your benefits!
807 475	Option package "Compressor (made by Bizer)" Semi-hermetically sealed construction Suction-gas-cooled motor Self-regulating oil sump heater	• Secure operation at higher ambient temperatures • Low maintenance • No risk of overheating • Ensures lubrication during the start • Very good availability of spare parts worldwide
807 586 807 609	Options packages "Corrosion protection" Corrosion protection package 1 Corrosion protection package 2	• Multiple-coated pipes • Housing / Plate parts made of high-quality stainless steel 1.4571 / AISI 316Ti • Multiple-coated pipes
807 789 807 779 807 780	Options packages "Air duct" Air duct bend galvanised steel Air duct bend primed and powder coated RAL7035 Air duct bend incl. fresh air primed and powder coated RAL7035	• Simple and fast connection to the cooling room • Suitable for outdoor installation • Simple and fast connection to the cooling room • Optically appealing coloring with high corrosion protection • Suitable for outdoor installation • Filtered fresh air supply, non-adjustable air volume • Optically appealing coloring with high corrosion protection
807 670	Option package "Custom" Customer-specific version	Special requirements of a company can be realized, such as: • Custom voltages / Network configurations • Heat exchanger version (fully copper, blade spacing and thickness) • Conductor identification • Special coatings • Protection class
807 674 807 678	Options packages "Accessories" Assembly accessories according to specification Spare parts according to specification	• Air duct, holding devices, refrigerating accessories • Spare part package

Plant packages:

<i>Material order no.</i>	<i>Scope of delivery</i>	<i>Your benefits!</i>
807 562	Plant package “Overpressure / Fresh air” Filter/Overpressure unit FT15	• Filtered fresh air supply, adjustable air volume • Creation of overpressure in the room to be cooled; less dust comes in
807 565	Plant package “Condensation evaporator” Condensation evaporator KVV	• No damage due to dripping condensation • No additional power supply necessary • Overload protection

Technical specifications TW3:

Performance data

Cooling performance is included customized in the offer

Nominal cooling performance:

4.6 kW | 15,700 btu/h

- At 80 °F (27 °C) room temperature, 52 % rel. room air humidity
95 °F (35 °C) ambient temperature
- Refrigerant R134a / R513A
-

Heating capacity

3.5 kW | 11,945 btu/h

Wide heating power on request

Air flow volume:

800 m³/h | 470 cfm

Cooling mode

- Depends on the compressor model size and version
- Depends on the option packages and version of heat exchanger

Temperature range R134a

-5 °C to +60 °C | +25 °F to +140 °F

Temperature range R513A

-5 °C to +60 °C | +25 °F to +140 °F

Temperature range R450A

-5 °C to +80 °C | +25 °F to +175 °F

Heating mode

Temperature range

-25 °C to +30 °C | -15 °F to +85 °F

Sizes and weight

Weight

approx. 180 kg | 400 lb

Dimensions

type, see dimension sheet

Operating voltage

Further operating voltages upon request

3 ph / 400 V / 50 Hz

3 ph / 460 V / 60 Hz

Refrigerant

GWP (global warming potential)

R134a / R513A / R450A

1430 / 631 / 605

Filling quantity / CO2 equivalent

depends on the unit version

Subject to technical change.