

TECHNICAL DESCRIPTION
CRANEFRIGOR™ TY

Date: 11.12.2023
QVO 0461-US
Rev. 03

Technical support: **e-mail:** sales@frigortecamericas.com / **phone:** +1 / (832) 730 - 1894



Figure

CRANEFRIGOR™ TY

The CRANEFRIGOR™ TY cooling unit was developed for reliable and long-term operation under extreme ambient conditions as in steel works, paper factories and foundries. Thanks to its robust structure, a reliable operation is ensured even with heavy shocks.

The CRANEFRIGOR™ series of crane air conditioning units ensure a reliable and efficient production process.

General description

Scope of delivery	Your benefits!
Refrigerant • Ecological refrigerant • Low greenhouse warming potential	• Sustainable operation
Compressor (made by Copeland) • Hermetically sealed construction • Suction-gas-cooled motor • Self-regulating oil sump heater	• Low maintenance • No risk of overheating • Ensures lubrication during the start • Very good availability of spare parts worldwide
Liquefier • Cathodic dip coating	• High corrosion resistance • Shorter maintenance intervals due to special adapted spacing between blades even with extreme dust load • Shorter maintenance intervals due to smooth surface
Liquefier fan • Speed-controlled EC axial fan in industrial construction for high ambient temperatures	• Powerful • Long runtimes • Energy-efficient
Evaporator • Zinc-plated steel housing with epoxy-coated aluminum blades • Cleaning opening / Inspection opening	• Excellent heat transfer • Shorter maintenance intervals due to special adapted spacing between blades even with extreme dust load • Shorter maintenance interval due to smooth surface. Soiling is easily recognized and simple to clean through the opening
Circulating air fan • Speed-controlled EC radial fan, industrial construction	• Powerful • Long runtimes • Energy-efficient and quiet
Air filter • Large-area frame filter • Filter class COARSE 90%	• Effective filter with long service life • Easy to replace and clean
Condensation water separation • Drip tray primed and powder-coated in RAL 3004 • Hose connection for condensation • Siphon in condensate line	• No corrosion of the tray • Defined condensation drainage • Avoids the drawing in of contaminated ambient air
Control and power cabinet • Completely wired, according to VDE • Temperature control by thermostat • Operational and fault signal outputs • Powder-coated RAL 7035 • Optional stainless-steel version	• The CRANEFRIGOR™ is ready for connection; at the site, you only have to connect the power supply • Color scheme with high corrosion protection
Casing • Robust, welded construction • Primed and powder-coated in RAL 3004 • Other colors or stainless-steel version optional	• Long service life • Attractive colour scheme with high corrosion protection
Quality assurance • Leakage test • Function test in our plant's test facility	• Operational reliability • Easy commissioning on site

Options packages:

Material order no.	Scope of delivery	Your benefits!
807 639	Option package “Compressor (made by Bizer)” Semi-hermetically sealed construction Suction-gas-cooled motor Self-regulating oil sump heater	- Secure operation at higher ambient temperatures - Low maintenance - No risk of overheating - Ensures lubrication during the start - Very good availability of spare parts worldwide
807 642	Option package “Heater” Air heater with temperature monitor	- Comfortable room temperature - Frost protection even at standstill or during maintenance work
807 643	Option package “Operational reliability” Low outside temperature	Cooling during outside temperature <60 °F (<15 °C)
807 648 807 652	Options packages “Corrosion protection” Corrosion protection package 1 Corrosion protection package 2	- Multiple-coated pipes - Housing / Plate parts made of high-quality stainless steel 1.4571 / AISI 316Ti - Multiple-coated pipes
807 778	Option package “Air duct” 90° bend incl. filter Filter class COARSE 80%	Simple and fast connection to the cooling room
807 656	Option package “Custom” Customer-specific version	Special requirements of a company can be realised, such as: - Custom voltages / Network configurations - Heat exchanger version (fully copper, blade spacing and thickness) - Conductor identification - Special coatings - Protection class
807 660 807 664	Options packages “Accessories” Assembly accessories according to specification Spare parts according to specification	- Air duct, holding devices, refrigerating accessories - Spare part package

Plant packages:

Material order no.	Scope of delivery	Your benefits!
807 665 807 562	Plant packages “Overpressure / Fresh air” Fresh air supply on the device Filter/Overpressure unit FT15	- Filtered fresh air supply, air volume not adjustable - Filtered fresh air supply, adjustable air volume - Creation of overpressure in the room to be cooled; less dust comes in
807 565	Plant package “Condensation evaporator” Condensation evaporator KVV	- No damage due to dripping condensation - No additional power supply necessary - Overload protection

Technical specifications TY:

Performance data

Cooling performance is included customized in the offer

Nominal cooling performance:

- At 80 °F (27 °C) room temperature, 52 % rel. room air humidity
- 95 °F (35 °C) ambient temperature
- Refrigerant R134a / R513A

6.4 kW | 21,840 btu/h

Heating capacity

Wide heating power on request

3.5 kW | 11,945 btu/h

Air flow volume:

1,000 m³/h | 590 cfm

Cooling mode

- Depends on the compressor model size and version
- Depends on the option packages and version of heat exchanger

Temperature range R134a

With option package "low outside temperature"

-5 °C to +70 °C | +25 °F to +160 °F

-25 °C to +70 °C | -15 °F to +160 °F

Temperature range R513A

With option package "low outside temperature"

-5 °C to +70 °C | +25 °F to +160 °F

-25 °C to +70 °C | -15 °F to +160 °F

Temperature range R450A

With option package "low outside temperature"

-5 °C to +80 °C | +25 °F to +175 °F

-25 °C to +80 °C | -15 °F to +175 °F

Heating mode

Temperature range

-25 °C to +30 °C | -15 °F to +90 °F

Sizes and weight

Weight

Dimensions

approx. 180 kg | 400 lb

type, see dimension sheet

Operating voltage

Further operating voltages upon request

3 ph / 400 V / 50 Hz

3 ph / 460 V / 60 Hz

Refrigerant

GWP (global warming potential)

R134a / R513A / R450A

1430 / 631 / 605

Filling quantity / CO2 equivalent

depends on the unit version

Subject to technical change.