

TECHNICAL DESCRIPTION
CRANEFRIGOR™ VX

Date: 27.01.2022
QVO 0446-US
Rev. 03

Technical support: **e-mail:** sales@frigortecamericas.com / **phone:** +1 / (832) 730 - 1894



Figure

CRANEFRIGOR™ VX

The CRANEFRIGOR™ VX liquefier was developed for reliable and long-term operation under extreme ambient conditions as in steel works, paper factories and foundries. Thanks to its robust structure, a reliable operation is ensured even with heavy shocks.

The CRANEFRIGOR™ series of crane air conditioning units ensure a reliable and efficient production process.

The condensing unit CRANEFRIGOR™ VX is only approved for evaporating temperatures $>15^{\circ}\text{F}$ ($> -10^{\circ}\text{C}$) and is therefore not covered by Ecodesign Directive 2009/125/EC.

General description

Scope of delivery	Your benefits!
Compressor (made by Bizer) - Semi-hermetically sealed construction - Suction-gas-cooled motor - Self-regulating oil sump heater	- Low maintenance - No risk of overheating - Ensures lubrication during the start - Very good availability of spare parts worldwide
Liquefier Cathodic dip coating	- High corrosion resistance - Shorter maintenance intervals due to special adapted spacing between blades even with extreme dust load - Shorter maintenance intervals due to smooth surface
Liquefier fan Speed-controlled EC axial fan in industrial construction for high ambient temperatures	- Powerful - Long runtimes - Energy-efficient
Casing - Robust, welded construction - Primed and powder-coated in RAL 3004 - Other colors or stainless-steel version optional	- Robust, welded construction - Primed and powder-coated in RAL 3004 - Other colors or stainless-steel version optional
Terminal box - Completely wired according to VDE - Powder-coated RAL 7035 - Optional stainless-steel version	- The CRANEFRIGOR™ is wired connection-ready on a terminal strip. - Colour scheme with high corrosion protection
Quality assurance - Leakage test - Presetting of the safety devices	- Operational reliability - Easy commissioning on site

Options packages:

Material order no.	Scope of delivery	Your benefits!
8807 529	Option package “Operational reliability” Low outside temperature	Cooling during outside temperature <15 °F (< -5 °C)
807 538 807 344	Options packages “Corrosion protection” Corrosion protection package 1 Corrosion protection package 2	- Multiple-coated pipes - Housing / Plate parts made of high-quality stainless steel 1.4571 / AISI 316Ti - Multiple-coated pipes
807 550	Option package “Custom” Customer-specific version	Special requirements of a company can be realized, such as: - Custom voltages / Network configurations - Liquefier version (fully copper, blade spacing and thickness) - Conductor identification - Special coatings - Protection class

Plant packages:

Material order no.	Scope of delivery	Your benefits!
807 571	Plant packages “Electrical control” Constructed as switchboard or control cabinet • Completely wired, according to VDE • Operational and fault signal outputs • Powder-coated RAL 7035 (control cabinet)	• Adjustable to individual specifications
807 572	Optional stainless-steel version (Control cabinet)	• Increased corrosion protection
807 565	Plant package “SMART Control” Superordinate controller FrigorTec Smart Control FSC	• Cyclic switching over for redundant systems • Digital display of pressures and temperatures • Optional regulation of the room pressure by filter/overpressure unit • Optional display of the relative room humidity
807 573	Plant packages “Internal unit (Evaporator)” Wall or ceiling version • Operation of several internal units on one liquefier possible • Epoxy-coated blades • Housing primed and powder-coated	• Adjustment options as required for the project • Color scheme with high corrosion protection
805 573	Optional housing in stainless steel version	• Increased corrosion protection
807 562	Plant packages: “Overpressure / Fresh air” Filter/Overpressure unit FT15	• Filtered fresh air supply, adjustable air volume • Creation of overpressure in the room to be cooled; less dust comes in
807 563	Self-cleaning filter/overpressure unit FS10	• Long filter service life due to fully automatic shaking function • Filtered fresh air supply, adjustable air volume • Creation of overpressure in the room to be cooled; less dust comes in
807 579	Plant package “Condensation evaporator” Condensation evaporator KV1	• No damage due to dripping condensation • No additional power supply necessary • Overload protection
807 575	Plant package “Assembly material” • Refrigerant lines made of copper • Solenoid valves, expansion valves, filter drier, sight glasses • Thermostats • Insulation for suction line • Refrigerant • Plumb-line	• Adjustments and planning as required for the project must be made in advance.

Technical specifications VX:

Performance data

Cooling performance is included customized in the offer

Nominal cooling performance:

6.4 kW | 21,850 btu/h

- At 80 °F (27 °C) room temperature, 52 % rel. room air humidity
95 °F (35 °C) ambient temperature
- Refrigerant R134a / R513A

Cooling mode

- Depending on compressor size
- Depends on the option packages and version of heat exchanger

Temperature range R134a

-5 °C to +70 °C | +25 °F to +160 °F

With option package "low outside temperature"

-25 °C to +70 °C | -15 °F to +160 °F

Temperature range R513A

-5 °C to +70 °C | +25 °F to +160 °F

With option package "low outside temperature"

-25 °C to +70 °C | -15 °F to +160 °F

Temperature range R450A

-5 °C to +70 °C | +25 °F to +160 °F

With option package "low outside temperature"

-25 °C to +85 °C | -15 °F to +185 °F

- More extreme temperatures upon request

Sizes and weight

Weight

approx. 70 kg | 155 lb

Dimensions

type, see dimension sheet

Operating voltage

Further operating voltages upon request

3 ph / 400 V / 50 Hz

3 ph / 460 V / 60 Hz

Refrigerant

GWP (global warming potential)

R134a / R513A / R450A

1430 / 631 / 605

Filling quantity / CO2 equivalent

depends on the unit version

Subject to technical change.